

Bondthane™ Application Selector Chart

PRODUCT	PROPERTIES				COATINGS											ADHESIVES		
	CO-SOLVENT FREE	NMP FREE	WEIGHT SOLIDS %	ELONGATION PERCENTAGE	SWARD HARDNESS	WOOD FLOORING	WOOD FURNITURE	RIGID VINYL COATINGS	METAL COATINGS	RIGID PLASTIC COATINGS	FLEXIBLE VINYL \ PVC	LEATHER FINISHES	TEXTILE COATINGS	INKS & OPV'S	BONDED LEATHER	HEAT SEAL ADHESIVES	LAMINATING ADHESIVES	SEALANTS
UD-104	●	●	38	400	12						●		●			●	●	●
UD-108	●	●	33	525	4								●			●	●	●
UD-125			33	1000	2												●	
UD-211			35	400	18					●	●	●		●	●			
UD-215		●	35	350	18					●	●	●		●	●			
UD-220			35	200	38	●	●	●	●	●								
UD-238			35	560	10					●	●				●			
UD-250			35	200	30	●	●	●	●	●				●				
UD-255		●	35	135	30	●	●	●	●	●								
UD-263			35	350	22			●	●	●	●	●		●	●			
UD-270			40	500	10					●	●	●	●	●	●			
UD-275		●	35	635	8					●	●	●	●	●	●			
UD-295			34	160	36			●		●				●				
UD-301			40	600	6					●	●	●		●	●	●	●	●
UD-302	●	●	40	500	4							●	●				●	
UD-303	●	●	35	730	<4							●	●		●		●	
UD-312	●	●	35	510	8							●	●		●			
UD-315		●	40	650	8					●	●	●		●	●	●	●	●
UD-375	●	●	60	1000	<4							●	●	●	●			
UD-410	●	●	35	600	<4							●						
UD-420	●	●	40	370	<4							●						
UD-610			40	995	<4							●	●				●	●
UD-615			40	800	10					●	●	●	●	●				
UD-620			34	230	30	●	●	●	●	●				●				